

CY Electromagnic current and voltage transformers quotation form

Tick the appropriate box ✓ and fill in these the needed value									
Common characteristics									
Туре							Quantity		
Standard		GB	IEC		ANS	SI	Other		
Frequency		50 Hz	60 Hz				. M		
Highest voltage for equipment (kV)		7.2	12 17.5	24	40.5/3	6 72.5	Other		
Installation site		Indoor	Outdoor				~		
Height above & Sea-level		1000M	2000M		30001	4000M	Other		
VT's specifications									
Primary Phase type			Ph	ase / ground		Phase / phase			
Rated primary voltage	3		(kV)		,				
Secondary	1st secondary 2nd secondary 3rd secondary								
Rated secondary voltage	2		(V)			(V)		(V)	
Accuracy class			Class			Class		Cla	
Rated output	_		(VA)			(VA)		(VA	
CT's specifications									
or a specifications									
Rated primary current			A	Rated prim	nary voltage	e (k\	′)		
Rated short time current			(kA)						
Rated secondary current	5A	secondar	<u> </u>	1A	secondary		Other 3rd sec	ondary	
Accuracy class	ist secondary		Class		Class		3rd secondary		
Rated output			(VA)			(VA)		(V/	
			!(\(\daggregart\)		:	(*/1)		(*/	
Security factor (FS) / accuracy limit factor (ALF)	(FS/ALF)		(FS/ALF)				(FS/ALF)	(FS/ALF)	
	· · · · · ·		<u> </u>				· /1		
Other special requireme	nte					-	====		
Other special requireme	1113								