

GELPORT - Submersible Secondary Connectors for URD Distribution (1000 V)



GRPT-500 ORDERING INFORMATION

Gelport for 240mm ² cables	Number of Ports	Cable Sizes mm ²	Max Number ports to be used for 240mm ² cable	Min Number of ports to be used for 6mm ² -150mm ²	Max Number of ports to be used for 6mm ² -150mm ² (if no max cable used)	Length mm	Width mm	Height mm
GRPT-500-3P-C 5-1899241-7	3	16-240	1	2	3	117	97	89
GRPT-500-4P-C 5-1899241-8	4	16-240	2	2	4	149	97	89
GRPT-500-5P-C 5-1899241-9	5	16-240	3	2	5	180	97	89
GRPT-500-6P-C 5-1899241-0	6	16-240	4	2	6	212	97	89
GRPT-500-8P-C 5-1899241-1	8	16-240	6	2	8	276	97	89

GRPT-600 ORDERING INFORMATION

Gelport for 300mm ² Cables	Number of Ports	Cable Sizes mm ²	Max Number ports to be used for 300mm ² cable	Min Number of ports to be used for 16mm ² -185mm ²	Max Number of ports to be used for 16mm ² -185mm ² (if no max cable used)	Length mm	Width mm	Height mm
GRPT-600-3P-C	3	2 X 185-300 & 1 X 16-185	2	1	3	128	90	105

GRPT-350 ORDERING INFORMATION

Gelport for 150mm ² Cables	Number of Ports	Cable Sizes mm ²	Max Number ports to be used for 150mm ² cable	Length mm	Width mm	Height mm
GRPT-350-3P	3	6-150	3	117	97	89
GRPT-350-4P 7-1201146-7	4	6-150	4	149	97	89
GRPT-350-5P	5	6-150	5	180	97	89
GRPT-350-6P	6	6-150	6	212	97	89
GRPT-350-8P	8	6-150	8	276	97	89

Conductor Size mm ²	Recommended Torque settings
6-16 mm ²	15/20 Nm
25-185 mm ²	25/31 Nm
185-300 mm ²	31/40 Nm