

LV MULTI-PURPOSE CONNECTOR BLOCKS

XK2 connector blocks are designed for a wide variety of electrical systems. They are a perfect upgrade for busbars, traditional power distribution blocks and strip connections. The unique socket design provides customers safe and reliable installation.

FEATURES

- Provides hundreds of input/output combinations with internal and external parallel connection methods, giving wiring professionals remarkable flexibility
- Low-cost and reliable contact point design
- Supports 10mm²–300mm² in and 1mm²–50mm² out
- Can be mounted on TN 35 DIN rail or on base-plate
- Passed UL 94 V-0 flammability test
- IEC 60529 IP20 rated safety protection
- IEC standard colour code (blue, red, yellow, green, and yellow-green)
- Fit for IEC 60947-7-1



TNXK235/10X4 TNXK235/4X9



TNXK250/10X6 TNXK270/10X8 TNXK270/16X6 TNXK295/25X4 TNXK2120/16X8 TNXK2185/35X8

Cat No.	Voltage (V)	Amp Rating (A)	Input Cable Size	Output Cable Size & Quantity
TNXK235/10X4	690	125	10-35 mm ²	4 X 2.5-10 mm ²
TNXK235/4X9	690	125	10-35 mm ²	9 X 1-4 mm ²
TNXK250/10X6	690	150	16-50 mm ²	6 X 2.5-10 mm ²
TNXK270/10X8	690	192	25-70 mm ²	8 X 2.5-10 mm ²
TNXK270/16X6	690	192	25-70 mm ²	6 X 4-16 mm ²
TNXK295/25X4	690	232	25-95 mm ²	4 X 6-25 mm ²
TNXK2120/16X8	690	269	35-120 mm ²	8 X 4-16 mm ²
TNXK2185/35X8	690	353	70-185 mm ²	8 X 10-35 mm ²